



Precision Diagnostic Instruments

DM-930 Multimeter

The DM-930 is the next step in advanced Digital Multimeters, combining class leading accuracy and range with the unparalleled durability that comes along with IP67 design.



Safety Conformance:
IEC1010-1 EN61010-1,
CAT III 1000V, CAT IV 600V,
CLASS 2, Double Insulation



- Current
- AC Voltage
- DC Voltage
- Diode Test
- Continuity
- Frequency
- Resistance
- RPM (Tach)
- Dwell Angle
- Capacitance
- Temperature
- % Duty Cycle
- ms-Pulse Width
- Water & Dust Proof
- Peak, Max/Min, Hold

IP67 Durability

Accessories Included with DM-930



PDI 895 Multimeter

The PDI 895 brings all of the necessary functions of an Automotive Diagnostic Meter to an easy to use, reliable and economic package.



Safety Conformance:
IEC1010-1 EN61010-1,
CAT III 600V,
CLASS 2, Double Insulation



- Current
- AC Voltage
- DC Voltage
- Diode Test
- Continuity
- Frequency
- Resistance
- RPM (Tach)
- Dwell Angle
- Temperature
- % Duty Cycle
- Auto Power Off
- Analog Bar Graph
- Data Hold Function
- 3,000 Count Display

Accessories Included with PDI 895



Precision Diagnostic Instruments

7581 W. 103rd Ave - Westminster, CO 80021 Phone: 1-800-453-7892 Fax: (303) 650-1238

Copyright 2013 - PDI - All Right Reserved

MKTG# ADS5



CA-400D AC/DC Clamp

For use with PDI
895, 925 or 930

- AC or DC Current up to 400A
- Non-contact voltage detection
- Basic Accuracy $\pm 2.5\%$
- Measure current through wire insulation.
- Rate Output 0-400mv for 0-400A



CA-400A AC Clamp

For use with PDI
895, 925 or 930

- AC Current up to 400A
- Non-contact voltage detection
- Basic Accuracy $\pm 2.5\%$
- Measure current through wire insulation.
- Rate Output 0-400mv for 0-400A



CA-60 AC/DC Clamp

For use with PDI
895, 925 or 930

- DC Current 10mA - 60A
- AC Current 10mA - 60A
- Basic Accuracy $\pm 1.5\%$ to ± 8
- Frequency Response 40Hz-20KHz
- Rate Output 0-600mv for 0-60A



SC-55 Meter Case

Rigid back, meter case made of heavy-duty fabric with shoulder strap. Dual zipper opening for easy access to meter, probes and accessories. Velcro straps to secure and protect your tools.

9" h x 6" w x 3" d (closed)



SC-10 Soft Case

Durable, padded case made of heavy-duty fabric with shoulder strap. Large, zipper pocket for meters and clamp probes. Small zipper pocket for leads and accessories.

9 1/2" h x 10 1/2" w x 5" deep.



Replacement Fuses

Fuse Packs for 895, 925 or 930
Each fuse pack includes 5 low Amp fuses and 2 high Amp fuses for the specific meter.



IP-60 Immersion Probe

For use with 895, 925 or 930
Designed for immersion in liquids and gels.
Range: -40° to 800°F



5-Way Test Clip

For use with 895, 925 or 930
Heavy-duty clip lead with insulation piercer.
48" long with male banana plug



TP-03 Bead Probe

For use with 895, 925 or 930
Bead type temperature probe. Teflon coated K-type with molded-on strain relief